

# TABLEAU DE RÉGLAGE DU BY-PASS ET CAPACITÉS DE FILTRATION



## PURITY C Quell ST



by-pass fixe 0 %

Dureté carbonate °dH	Réglage by-pass conseillé	Capacités de filtration en litres				
		PURITY C50	PURITY C150	PURITY C300	PURITY C500	PURITY C1100
4	0%	1.000	2.508	4.167	7.083	11.979
5	0%	1.000	2.508	4.167	7.083	11.979
6	0%	1.000	2.508	4.167	7.083	11.979
7	0%	857	2.150	3.571	6.071	10.268
8	0%	750	1.881	3.125	5.313	8.984
9	0%	667	1.672	2.778	4.722	7.986
10	0%	600	1.505	2.500	4.250	7.188
11	0%	545	1.368	2.273	3.864	6.534
12	0%	500	1.254	2.083	3.542	5.990
13	0%	462	1.158	1.923	3.269	5.529
14	0%	429	1.075	1.786	3.036	5.134
15	0%	400	1.003	1.667	2.833	4.792
16	0%	375	941	1.563	2.656	4.492
17	0%	353	885	1.471	2.500	4.228
18	0%	333	836	1.389	2.361	3.993
19	0%	316	792	1.316	2.237	3.783
20	0%	300	753	1.250	2.125	3.594
21	0%	286	717	1.190	2.024	3.423
22	0%	273	684	1.136	1.932	3.267
23	0%	261	654	1.087	1.848	3.125
24	0%	250	627	1.042	1.771	2.995
25	0%	240	602	1.000	1.700	2.875
26	0%	231	579	962	1.635	2.764
27	0%	222	557	926	1.574	2.662
28	0%	214	538	893	1.518	2.567
29	0%	207	519	862	1.466	2.478
30	0%	200	502	833	1.417	2.396
31	0%	194	485	806	1.371	2.319
32	0%	188	470	781	1.328	2.246
33	0%	182	456	758	1.288	2.178
34	0%	176	443	735	1.250	2.114
35	0%	171	430	714	1.214	2.054

by-pass fixe 30 %

Dureté carbonate °dH	Réglage by-pass conseillé	Capacités de filtration en litres				
		PURITY C50	PURITY C150	PURITY C300	PURITY C500	PURITY C1100
4	30%	1.386	3.476	5.774	9.815	16.600
5	30%	1.386	3.476	5.774	9.815	16.600
6	30%	1.386	3.476	5.774	9.815	16.600
7	30%	1.188	2.979	4.949	8.413	14.228
8	30%	1.039	2.607	4.330	7.362	12.450
9	30%	924	2.317	3.849	6.544	11.066
10	30%	831	2.086	3.464	5.889	9.960
11	30%	756	1.896	3.149	5.354	9.054
12	30%	693	1.738	2.887	4.908	8.300
13	30%	640	1.604	2.665	4.530	7.661
14	30%	594	1.490	2.474	4.207	7.114
15	30%	554	1.390	2.310	3.926	6.640
16	30%	520	1.303	2.165	3.681	6.225
17	30%	489	1.227	2.038	3.464	5.859
18	30%	462	1.159	1.925	3.272	5.533
19	30%	438	1.098	1.823	3.100	5.242
20	30%	416	1.043	1.732	2.945	4.980
21	30%	396	993	1.650	2.804	4.743
22	30%	378	948	1.575	2.677	4.527
23	30%	361	907	1.506	2.561	4.330
24	30%	346	869	1.443	2.454	4.150
25	30%	333	834	1.386	2.356	3.984
26	30%	320	802	1.332	2.265	3.831
27	30%	308	772	1.283	2.181	3.689
28	30%	297	745	1.237	2.103	3.557
29	30%	287	719	1.195	2.031	3.434
30	30%	277	695	1.155	1.963	3.320
31	30%	268	673	1.118	1.900	3.213
32	30%	260	652	1.083	1.840	3.112
33	30%	252	632	1.050	1.785	3.018
34	30%	245	613	1.019	1.732	2.929
35	30%	238	596	990	1.683	2.846

Cartouche PURITY C en présence d'une tête de filtre 0-70% à by-pass variable

Dureté carbonate °dH	Réglage by-pass conseillé	Capacités de filtration en litres				
		PURITY C50	PURITY C150	PURITY C300	PURITY C500	PURITY C1100
4	70%	1.900	4.766	7.917	13.458	22.760
5	70%	1.900	4.766	7.917	13.458	22.760
6	70%	1.900	4.766	7.917	13.458	22.760
7	60%	1.821	4.569	7.589	12.902	21.819
8	50%	1.425	3.574	5.938	10.094	17.070
9	50%	1.267	3.177	5.278	8.972	15.174
10	40%	960	2.408	4.000	6.800	11.500
11	40%	873	2.189	3.636	6.182	10.455
12	30%	693	1.738	2.887	4.908	8.300
13	30%	640	1.604	2.665	4.530	7.661
14	30%	594	1.490	2.474	4.207	7.114
15	30%	554	1.390	2.310	3.926	6.640
16	30%	520	1.303	2.165	3.681	6.225
17	30%	489	1.227	2.038	3.464	5.859
18	30%	462	1.159	1.925	3.272	5.533
19	20%	387	970	1.612	2.740	4.634
20	20%	368	922	1.531	2.603	4.402
21	20%	350	878	1.458	2.479	4.193
22	20%	334	838	1.392	2.366	4.002
23	20%	320	802	1.332	2.264	3.828
24	20%	306	768	1.276	2.169	3.669
25	20%	294	737	1.225	2.083	3.522
26	20%	283	709	1.178	2.002	3.386
27	20%	272	683	1.134	1.928	3.261
28	20%	263	658	1.094	1.859	3.145
29	20%	253	636	1.056	1.795	3.036
30	20%	245	615	1.021	1.735	2.935
31	20%	237	595	988	1.679	2.840
32	20%	230	576	957	1.627	2.751
33	20%	223	559	928	1.578	2.668
34	20%	216	542	901	1.531	2.590
35	20%	210	527	875	1.488	2.516

Pour machines à café, espresso et distributeurs automatiques

Pour fours vapeur et fours traditionnels

4	10%	1.100	2.759	4.583	7.792	13.177
5	10%	1.100	2.759	4.583	7.792	13.177
6	10%	1.100	2.759	4.583	7.792	13.177
7	10%	943	2.365	3.929	6.679	11.295
8	10%	825	2.069	3.438	5.844	9.883
9	10%	733	1.839	3.056	5.194	8.785
10	10%	660	1.656	2.750	4.675	7.906
11	10%	600	1.505	2.500	4.250	7.188
12	10%	550	1.380	2.292	3.896	6.589
13	10%	508	1.273	2.115	3.596	6.082
14	10%	471	1.183	1.964	3.339	5.647
15	10%	440	1.104	1.833	3.117	5.271
16	10%	413	1.035	1.719	2.922	4.941
17	10%	388	974	1.618	2.750	4.651
18	10%	367	920	1.528	2.597	4.392
19	10%	347	871	1.447	2.461	4.161
20	10%	330	828	1.375	2.338	3.953
21	10%	314	788	1.310	2.226	3.765
22	10%	300	753	1.250	2.125	3.594
23	10%	287	720	1.196	2.033	3.438
24	10%	275	690	1.146	1.948	3.294
25	10%	264	662	1.100	1.870	3.163
26	10%	254	637	1.058	1.798	3.041
27	10%	244	613	1.019	1.731	2.928
28	10%	236	591	982	1.670	2.824
29	10%	228	571	948	1.612	2.726
30	10%	220	552	917	1.558	2.635
31	10%	213	534	887	1.508	2.550
32	10%	206	517	859	1.461	2.471
33	10%	200	502	833	1.417	2.396
34	10%	194	487	809	1.375	2.325
35	10%	189	473	786	1.336	2.259